

BRAND:	Fiberlogy
NAME:	<b>Fiberlogy PP</b>
MANUFACTURER:	Fiberlab S.A., Brzezie 387, 32-014 Brzezie, Poland
DESCRIPTION:	PP filament designed for printing in FFF/FDM technology, available in different colors, wound on a spool, vacuum-packed in plastic, placed in a cardboard box.

**TECHNICAL INFORMATION:**

Diameter:	1.75 mm
Diameter Tolerance:	+/- 0.02 mm
Avg Roundness:	+ 0.01 mm
Net Weight:	0.75 kg
Print Temperature:	220°C - 250°C
Bed Temperature:	0°C - 80°C

**MATERIAL PROPERTIES:**

Mechanical Properties	Test Method	Unit	Typical Value
Density	ISO 1183	g/cc	1.04
Tensile strength	ISO 527	MPa	>15
Elongation at break	ISO 527	%	>30
Tensile modulus	ISO 527	MPa	900
Charpy notched impact strength	ISO 179	kJ/m <sup>2</sup>	20
Thermal Properties	Test Method	Unit	Typical Value
Heat Distortion Temperature	ISO 75	°C	65

The information set forth herein has been gathered from standard reference materials and/or supplier test data. To the best knowledge and belief of Fiberlab S.A. they are accurate and reliable. Information is offered only for your consideration, investigation and verification. Fiberlab S.A. makes no warranties, expressed or implied, with respect to the use of such information or the use of the specific material identified herein combination with any other material or process, and assumes no responsibility therefore.

Last update: November 15, 2019